

## Tabela Maciço Laminado

SAE1020 / 1045 / 41/40 / 8620

POL.	Mm	Kg/MT
1/4	6,35	0,25
3/8	9,53	0,56
1/2	12,70	0,99
5,8	15,87	1,55
3/4	19,05	2,24
7,8	22,23	3,04
• 1	25,40	3,97
• 1.1/8	28,57	5,03
• 1.1/4	31,75	6,21
• 1.3/8	34,92	7,51
• 1.1/2	38,10	8,94
• 1.5/8	41,27	10,49
• 1.3/4	44,45	12,17
• 1.7/8	47,62	13,97
• 2	50,80	15,90
• 2.1/8	53,97	17,95
• 2.1/4	57,15	20,12
• 2.3/8	60,32	22,42
• 2.1/2	63,50	24,84
• 2.5/8	66,67	27,38
• 2.3/4	69,85	30,05
• 2.7/8	73,02	32,85
• 3	76,20	35,77
• 3.1/4	82,55	41,88
• 3.1/2	88,90	46,68
• 3.3/4	95,25	55,88
• 4	101,60	63,58
4.1/4	107,90	71,78
4.1/2	114,30	80,47
4.3/4	120,60	89,66
5	127,00	99,80
5.1/4	133,30	109,50
5.1/2	139,70	120,20
5.3/4	146,00	131,40
6	152,40	143,10
6.1/4	158,70	155,20
6.1/2	165,10	167,90
6.3/4	171,45	181,10